

# MATERIAL SAFETY DATA SHEET

**U-MARK, Inc.**

Rev. Date: November 15, 2006

## **PRODUCT NAME: 300P INDUSTRIAL PAINT MARKER**

### **1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION**

Product Identifier: 300P Industrial Paint Marker

General Use: Marking on Most Surfaces

Product Color: Black, Blue, Medium Blue, Brown, Green, Bright Green, Orange, Pink, Red, Violet, White, Yellow.

**Conforms to ASTM D4236:** These markers and the inks contained within have been examined by a certified toxicologist to assure they comply with the Federal Hazardous Substance Act (FHSA) and the Labeling of Hazardous Art Materials Act (LHAMA), in accordance with ASTM D-4236.

**U-Mark, Inc., 102 Iowa Avenue, Belleville, IL 62220 USA tel. 618-235-7500**

**24-hour Emergency Phone: Infotrac 1-800-535-5053 (within the USA and Canada), 1-352-323-3500 (International)**

### **2. COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENT	CAS No.	% by Wt.	Exposure Limits (ppm)	
			OSHA TWA	ACGIH TWA
Xylene	1330-20-7	30-50	100	100
Ethylbenzene	100-41-4	2-10	100	100

### **3. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW: Flammable liquid and vapor. May cause eye, skin and respiratory tract irritation. May affect central nervous system. If swallowed, do not induce vomiting. Get immediate medical attention.**

#### **POTENTIAL HEALTH EFFECTS:**

**INHALATION:** Overexposure may cause headache, dizziness and other central nervous system effects. May irritate the respiratory tract.

**EYE CONTACT:** May cause irritation, redness, tearing, and blurred vision.

**SKIN CONTACT:** May cause mild irritation, redness, defatting, and dermatitis.

**INGESTION:** May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**CHRONIC:** Does not contain materials listed as cancer causative agents by NTP or OSHA. IARC (International Agency for Research of Cancer) has classified Ethylbenzene as a possible human carcinogen (2B). Long Term overexposure may cause liver and kidney damage.

### **4. FIRST AID MEASURES**

**INHALATION:** Remove to fresh air. If breathing has stopped, apply artificial respiration and call a physician immediately.

**EYE CONTACT:** Immediately flush eyes with plenty of water and call a physician immediately.

**SKIN CONTACT:** Wash with soap and water. Remove contaminated clothing and launder before use.

**INGESTION:** Get medical attention immediately. Do not induce vomiting unless directed by a physician.

### **5. FIRE FIGHTING MEASURES**

#### **FLAMMABLE PROPERTIES:**

Flash Point: 75-85°F (24-29°C) Method: TCC Flammable Limits: LEL 1% UEL 7%

Auto-ignition Temperature: Not Available

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, unidentified organic compounds.

**EXTINGUISHING MEDIA:** Alcohol foam, dry chemical, CO<sub>2</sub>.

**FIRE FIGHTING INSTRUCTIONS:** Use self-contained breathing apparatus and full protective clothing when large amounts are involved. A stream of water may help to spread the fire.

**6. ACCIDENTAL RELEASE MEASURES**

Remove all ignition sources and ventilate area. Absorb spilled material and place in a container for disposal (e.g. incineration.) Dispose of in accordance with all Federal, State and local regulations.

**7. HANDLING AND STORAGE**

**HANDLING:** Wash thoroughly after handling.

**STORAGE:** Store away from heat, sparks, or flames. Store between 40° and 120° F (4° and 49° C.)

**8. EXPOSURE CONTROL/PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** General ventilation is recommended to keep vapors below exposure limits

**RESPIRATORY PROTECTION:** use a NIOSH/MSHA approved respirator equipped for organic vapors if exposure limits are exceeded.

**SKIN PROTECTION:** Wear impervious gloves if hand contact is anticipated.

**EYE PROTECTION:** Not normally required if used as intended. Wear chemical splash goggles in compliance with OSHA if splashing is possible.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**BOILING RANGE:** 246 – 404°F (119 – 207°C)      **MELTING POINT:** Not applicable

**VAPOR PRESSURE:** 5-7 mm Hg (68°F)      **VAPOR DENSITY:** >1

**SOLUBILITY IN WATER:** 0%      **SPECIFIC GRAVITY:** ~0.9

**ODOR:** Hydrocarbon.      **VOC:** 520-650 g/l

**APPEARANCE:** Colored, opaque liquid.      **% VOLATILE BY VOLUME:** 40-65

**10. STABILITY AND REACTIVITY**

**CHEMICAL STABILITY:** (Conditions to avoid) Ignition sources.

**INCOMPATIBILITY:** Strong oxidizing agents, inorganic acids, strong caustics, amines, ammonia.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Hydrocarbons

**HAZARDOUS POLYMERIZATION:** Will not occur.

**11. TOXICOLOGICAL INFORMATION**

1330-20-7 Xylene: Oral LD<sub>50</sub> 4.3g/kg. (Rat); Dermal LD<sub>50</sub> 2.0g/kg. (Rabbit.)

100-41-4 Ethylbenzene: Oral LD<sub>50</sub> 3.5g/kg. (Rat); Dermal LD<sub>50</sub> 17.8g/kg. (Rabbit.)

**12. ECOLOGICAL INFORMATION**

Prevent any run-off from reaching natural waterways.

**13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all applicable Federal, State and local regulations.

**14. TRANSPORT INFORMATION**

IATA, IMDG, DOT: Printing Ink, 3, UN 1210, PG III, ltd. Qty.

USA GROUND SHIPMENTS: Consumer Commodity, ORM-D

**15. REGULATORY INFORMATION**

EPCRA (SARA) Sec. 313 Reportable Materials: Xylenes, CAS No. 1330-20-7 and Ethylbenzene CAS No.

100-41-4. California Proposition 65 WARNING: This product contains a chemical known to the State of California to cause cancer (Ethylbenzene.)

**16. OTHER INFORMATION**

HMIS Hazard Rating: Health 2, Fire 3, Reactivity 0

NFPA Hazard Rating: Health 2, Fire 3, Reactivity 0

(4=extreme, 3=high, 2=moderate, 1=slight, 0=least).

**Caution!**

Information presented herein has been compiled from sources that we believe to be reliable and is accurate to the best of our knowledge and belief but its accuracy is not guaranteed. We have no control over the use or storage of our products; therefore we cannot assume any responsibility or liability in connection with the use or inability to use them. Specifically, our products and MSDS are supplied under the condition that Buyers and Users test our products for their intended use and make their own decision of suitability. Responsibility for compliance with all applicable Federal, State or local laws and regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.